

# 4000 SERIES SIT-DOWN COUNTERBALANCED TRUCKS

(4460/4750)

Raymond 4000 Series sit-down counterbalanced trucks offer the comfort, durability and maneuverability to efficiently handle a wide array of tasks around the warehouse, particularly in confined spaces such as trailers, ramps and stacking areas. Powerful, reliable and adaptable, these 3 and 4-wheel electric vehicles can be perfectly tailored to your specific needs with a variety of capacities, configurations, masts and attachments.

- + **Versatility:** Optimize performance in applications ranging from bulk and block storage to trailer loading/unloading and racking with flexible configuration options.
- + **Maintainability:** Increase uptime and decrease maintenance costs with vehicles that deliver more performance per battery charge and feature fewer wearable parts.
- + **Ergonomics:** Enhance operator comfort and productivity with a spacious, easy-to-access compartment that includes a fully adjustable, full suspension, cushioned seat, tilt steering wheel, and ergonomically placed controls.
- + **Visibility:** Superior visibility improves operator comfort and confidence. The open view mast gives the operator a clear line of sight to the load for increased efficiency and reduced product damage.
- + **Stability:** Assist operators with protecting your goods and facilities with the Raymond Performance Stability System that automatically regulates tilt speed when the mast is out of free lift for optimal control.



| SPECIFICATIONS:             | 4460 (3-WHEEL)                     | 4750 (4-WHEEL)                          |
|-----------------------------|------------------------------------|---|
| Voltage                     | 36 or 48V                          | 36 or 48V                               |
| Capacity                    | 3,000 – 4,000 lbs.                 | 3,000 - 12,000 lbs.                     |
| Height: 3-Stage Mast        | 227"                               | 233"*                                   |
| Height: 4-Stage Mast        | 276"                               | 278"                                    |
| Travel speed (unloaded)     | 9.9* mph (36V) 9.6-10.2* mph (48V) | 8.1-11.5* mph (36V) 9.3-12.0* mph (48V) |
| Turning Radius <sup>†</sup> | 55.1" - 62.8"*                     | 66.3" - 96.1"*                          |

<sup>†</sup>includes integral side shifter \*based on truck capacity

IF YOU'RE LOOKING FOR A PARTNER WITH THE TOOLS AND EXPERIENCE TO HELP YOU RUN BETTER AND MANAGE SMARTER, CONTACT US TODAY AT 1-800-235-7200 OR VISIT US AT RAYMONDCORP.COM

# RAYMOND