RBS26-S

LITHIUM-ION STRADDLE STACKER

Ideal for light-duty applications, the 2,600 lb. capacity, lithium-ion-powered RBS26-S gives you a highly maneuverable, productive stacker capable of lifting loads as high as 140".

User and application friendly, the RBS26-S features electric lift, lower, and travel to increase operator productivity, as well as adjustable base legs to suit multiple pallet sizes and aisle widths.

IDEAL APPLICATIONS:

+ LIGHT-DUTY GENERAL MATERIAL HANDLING
+ STACKING
+ PALLET HANDLING IN TIGHT AREAS

PRODUCTIVITY

+ Electric travel, lift, and lower enhance productivity.
+ Lithium-ion battery offers fast charging and long run times.
+ Opportunity charging keeps the trucks on the floor.

MANEUVERABILITY

+ Turtle Speed Button simplifies handling in tight spaces.
+ Creep mode allows travel with handle in vertical position.
+ Dual thumb controls offer comfortable operation for left- or right-handed users.

SECURITY

+ PIN code access requires no key and prevents unauthorized use.
+ Reduced speed in turns minimizes truck, product, and facility damage.
+ Load backrest (standard) enhances load stability and handling.

If you're looking for a partner with the tools and experience to help you run better and manage smarter, contact us today at 1-800-235-7200 or visit us at raymondcorp.com.

RAYMOND BASICS

GIVE YOURSELF THE ADVANTAGE IN SERVICE AND SUPPORT.

Available through your local Raymond Solutions and Support Center, the RBS26-S comes backed by the most extensive and experienced network of professionals in the industry.

Far beyond just lift trucks, we offer complete intralogistics solutions, helping you optimize your operation with a broad range of consulting, connected technologies, services, and material handling equipment.

Experience the ease and convenience of partnering with a single source provider for everything from training and rentals to maintenance, telematics, automation, and energy solutions. We're here to help you run better and manage smarter by getting the most out of every piece of equipment, every square foot of space, and every hour of labor.

COMMON OPERATIONS

+ Warehousing
+ Distribution
+ Home Centers
+ Retail/Grocery Stores
+ Auto Parts

QUICK SPECS

+ 2,600 lb. capacity
  (2,200 lb. over 126" lift height)
+ 24V/60Ah LIB
+ Travel speed: 2.6 - 2.8 mph
+ Run time: ~2 hrs
+ DC motor
+ Mast configurations:
  76"/112" two stage, no free lift
  90"/140" two stage, no free lift
+ Turning radius: 53"
+ Base leg widths (outside):
  46.5", 50.5", 54.5", 58.5"

THIS PRODUCT IS AVAILABLE FOR PURCHASE ONLINE. CREATE AN ACCOUNT TO GET STARTED TODAY!
PORTAL.RAYMONDCORP.COM

©2026 The Raymond Corporation
Printed in USA
RB-1003B 1026

Due to continuous product improvement, specifications are subject to change without notice or obligation. Some systems and features shown are optional at extra cost. Raymond is a U.S. trademark of The Raymond Corporation.

RAYMOND
BASICS