RAYMOND
BASICS

PO Box 130
Greene, New York 13778-0130

Toll free 1-800-235-7200
Fax 1-607-656-9005

www.raymondcorp.com

©2026 The Raymond Corporation
Printed in USA
SIPB-1094K 1026

This guide merely highlights certain features of the described products. Additional information is available from product specific brochures and your authorized Raymond Solutions and Support Centers. Due to continuous product improvement, specifications are subject to change without notice. Some features shown are optional at extra cost. Raymond is a U.S. trademarks of The Raymond Corporation.

PRODUCT REFERENCE GUIDE

RAYMOND
BASICS

BUILT RIGHT. PRICED RIGHT.

USER FRIENDLY, BUDGET FRIENDLY SOLUTIONS.

From material handling to facility maintenance, these everyday solutions can help you perform a variety of tasks more quickly, easily and securely. In stock and available for quick shipment through our nationwide network of Sales & Service Centers, Raymond Basics can be in your hand - and on your floor - fast. Take your business to the next level with a line of solutions offering a unique combination of reliability, durability and affordability.

LITHIUM-ION WALKIE

+ Quick battery changes optimize uptime
+ Opportunity charging minimizes downtime
+ Key pad access prevents unauthorized use

RBW45

Load Capacity: 3,300 lbs. or 4,500 lbs.

Fork Length: 36" or 45.3"

Fork Overall Width: 21" or 27"

Battery: 24 volt/ 20 Ah
or 24 volt/ 36 Ah
or 48 volt / 20Ah (4,500 lbs.)

LITHIUM-ION STRADDLE STACKER

+ Electric travel, lift, and lower enhance productivity.
+ Dual thumb controls offer comfortable operation for left - or- right handed users.
+ Load backrest (standard) enhances load stability and handling.
+ Ideal for applications needing adjustable baselegs to accommodate different sized pallets.

RBS26-S

Load Capacity: 2,600 lbs.
(2,200 lbs for 140" mast)

Travel Speed: 2.6 - 2.8 mph

Battery: 24V/60Ah LIB

Mast Heights: 112", 140"

LITHIUM-ION FORK OVER STACKER

+ Electric travel, lift, and lower enhance productivity.
+ Dual thumb controls offer comfortable operation for left- or right-handed users.
+ Load backrest (standard) enhances load stability and handling.
+ Ideal for applications where skids, platforms, or any pallets without bottom boards are used.

RBS26-F

Travel Speed: 2.6 - 2.8 mph

Battery: 24V/60Ah LIB

Mast type/size/capacities
Single stage / 92"/79" / 2500 lbs.

Two-stage / no free lift / 76"/114"
72" / 2600 lbs.
72" - 98" / 1780 lbs.
98" - 114" / 1480 lbs.

DRIVABLE WORK PLATFORM

+ Elevated, drivable work platform for orderpicking/stocking, facility maintenance and retail
+ Adjustable load tray- powered height adjust
+ Maintenance-free mast

RBSP

Operator Capacity: 286 lbs. (130 kg)

Load Tray Capacity: 198 lbs. (90 kg)

Load Deck Capacity: 249 lbs. (113 kg)

Elevated platform height/
workingheight:
Platform 118"/Working 190"
Platform 128"/Working 200"